

autotherm Cooling Systems Reliable – Efficient - Flexible

autotherm cooling systems Type AKL/AKW ensure reliable cooling of machines and processes and are both economical in operation and easy to handle. Developed and manufactured in Bad Königshofen and equipped with proven refrigeration technology - high-performance pumps, large-volume tanks and modern control systems - our systems stand for robust technology in continuous operation. Each unit manufactured at our Bad Königshofen site is thoroughly tested and complies with current European regulations. autotherm combines comprehensive standard equipment with the flexibility to adapt to your specific application.

Your advantages at a glance:

- Reliable cooling stable water temperatures for machines and processes
- **Robust technology** proven compinents, high-performance pumps, lage-volume tanks for a stable 24/7 operation
- User-friendly intuitive controls, easy access, practical design
- Simple commissioning delivered ready for connection and factory-tested
- Economical operation efficient design for continuous use
- Flexible customization from standard solutions to individual configurations
- **Direct contact with the manufacturer** development, production and service in Bad Königshofen





Technical Information

Туре	Cooling capacity [kW]*	Refrig eration	Consumer pump delivery pressure [bar] Delivery rate [Umin] Rated power output [kW]	Evaporator pump delivery pressure [bar] Delivery rate [Vmin] Rated power output [kW]	On-site security measures	Water tank Material Volume [l]	Water- connections IG	Width Depth Height [mm]
AKL 13	1,1	R290 R513A R454C	Wp 1.4 3,6	Common pump for the evaporator and consumer circuit	16A	Plastic 11	1/2"	440 700 675
AKL 25	3,0		42 0,46					480 700 780
AKL 44	4,0		Wp 3.4 3,7					570 850
AKL 56	5,2		70 0,46					860
AKL 61	6,1					Stainless steel	1"	660 890
AKL 81	8,0		Wp 3.5			35		1.200
AKL 100	10		4,6			Stainless steel		820 980
AKL 120	12		70 0,69			50		980
AKL 150	15					Stainless steel 70		1.150 1.100 1.590
AKL 200	19			Wp 5.3 2,8 105 0,69	32A	Stainless steel 150	1 1/4"	710
AKL250	24		Wp 5.6					1.385
AKL 300	29		6,4 105					1.454
AKL 365	37		1,05					1.070 1.520 1.792
AKL 460	46		W- 40.2	Wp 10.1 1,6 250 0,69	63A	Stainless	- 11/2"	920
AKL 600	57		Wp 10.3 5,0			steel 300		2.150 1.791
AKL 700	67		250 2,2			Stainless steel 350		1.070 2.450 1.791
AKL 800	77		Wp 15.3 5,5	Wp 15.1 1,8	80A S	Stainless steel	2"	1.190 3.000
AKL 1000	95		365 3,8	365 1,1		600		1.340